

ME Heating Immersion Circulator

Print Data Sheet



Order Information

Model:

Order no.: 9162000

ME

Available mains power: 230V / 50-60Hz 100-115V / 50-60Hz

Sales & Support:



Monday to Friday 7:30 am - 17:00 pm

JULABO Labortechnik GmbH Eisenbahnstrasse 45 77960 Seelbach/Germany Phone +49 7823 51-0 Fax +49 7823 2491

info@julabo.de www.julabo.de

Technical changes reserved. Pictures may differ from original.

Description

Heating Immersion Circulator for any bath tanks up to 50 liters

JULABO Heating Immersion Circulators are available for various bath tanks up to a capacity of 50 litres and come equipped with a bath clamp that fits onto all tanks with a wall thickness up to 26 mm. This clamp allows fast and problem-free assembling for existing as well as new bath tanks. The immersion depth is 16.5 cm (adjustable down to 14.5 cm). The immersed parts are made of high-quality stainless steel or plastic. The pump set, which is available as an accessory, provides pumping to external systems for provision of external temperature tasks. An integrated cooling coil for cooling-water connection is also available as an accessory.

Advantages

- o VFD COMFORT DISPLAY, resolution 0.1 °C
- o Keypad for setpoints, warning/safety values and menu functions
- o PID3 cascade temperature control
- o ATC3 3-Point-Calibration
- o Pt100 External sensor connection for measurement and control
- o SMART PUMP, electronically adjustable pump stages
- o Early warning system for low liquid level (DBGM 203 06 059.8)
- o Adjustable high temperature cut-out, visible via display
- o RS232 interface for online communication o Integrated programmer for 10 program steps

Technical Specifications	
Working temperature range	20 200 °C
Temperature control	PID, cascade
Temperature stability	±0.01 °C
Display	VFD
Display resolution	0.1 °C
Integrated programmer	available
Heater capacity	2000 W
Pump capacity	Pressure: 0,230,45 bar Flow rate: 11-16 l/min
Digital interfaces	RS232
External Pt100 sensor connection	available
Dimensions (W x L x H)	13 x 15 x 33 cm
Weight	4 kg
Ambient temperature	540 °C
Classification according to DIN 12876-1	3 (FL)

Miscellaneous

Installation cooling coil and pump set for external applications available as accessory.