

### Product Image



### Description

Water Bath with MICROPROCESSOR technology

The TW series offers high-quality water baths with MICROPROCESSOR technology and a temperature stability of  $\pm 0.2$  °C. The working temperature range offers many application possibilities, e.g. routine laboratory applications, temperature control of samples, incubations, dental applications, material testing, corrosion tests, tempering of cultures as well as temperature testing of food and luxury articles. The units are provided with overall splash-water protection and have a keypad for temperature settings and with temperature indication (LED) for easy operation. Dry-running protection as well as optical and acoustical warnings, and switch-off functions, offer maximum protection for sensitive goods which require to be temperature controlled. There are a wide range of accessories including test tube racks and lift-up Makrolon covers available.

### Advantages

- o MICROPROCESSOR technology with PID temperature control
- o Bright MULTI-DISPLAY (LED)
- o Seamless, splash-proof keypad
- o Splash-proof mains switch
- o Early warning system with high and low temperature limits
- o Drain screw for conveniently emptying the bath
- o Dry-running protection / safety temperature fixed at 130 °C
- o Wide range of accessories including lift-up Makrolon bath cover available

### Order Information

Model: TW2  
 Order no.: 9550102  
 Available mains power:  
 230V / 50-60Hz  
 115V / 60Hz

### Sales & Support:

+49 7823 51-190

Monday to Friday  
 7:30 am - 17:00 pm

JULABO Labortechnik GmbH  
 Eisenbahnstrasse 45  
 77960 Seelbach/Germany  
 Phone +49 7823 51-0  
 Fax +49 7823 2491

[info@julabo.de](mailto:info@julabo.de)

[www.julabo.de](http://www.julabo.de)

Technical changes reserved.  
 Pictures may differ from original.

### Technical Specifications

Working temperature range	20 ... 99.9 °C
Temperature control	PID
Temperature stability	$\pm 0.2$ °C
Display	LED
Display resolution	0.1 °C
Integrated programmer	not available
Heater capacity	1000 W
Bath opening / bath depth (W x L / D)	15 x 13 / 11 cm
Filling volume	1 ... 2 Liters
Dimensions (W x L x H)	17 x 16 x 26 cm
Weight	3,5 kg
Ambient temperature	5...40 °C
Classification according to DIN 12876-1	1

### Miscellaneous

Lift-up Makrolon cover available as accessory (order no. 8970289)